S&H Form: PTO/SB/05 (12/97)

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 1086.1107/JDH

First Named Inventor or Application Identifier:

Takashi MORIHARA, et al.

Express Mail Label No.

APPLICATION ELEMENTS *See MPEP chapter 600 concerning utility patent application contents.*	*ADDRESS TO:* **Assistant Commissioner for Patents Box Patent Application Washington, DC 20231**

1. [X] Fee Transmittal Form
2. [X] Specification, Claims & Abstract ..... [Total Pages: 56]
3. [X] Drawing(s) *(35 USC 113)* ..... [Total Sheets: 28]
4. [X] Oath or Declaration ..... [Total Pages: 4]
   a. [X] Newly executed (original or copy)
   b. [ ] Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional with Box 17 completed)*
      i. [ ] DELETION OF INVENTOR(S)
      Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. [ ] Incorporation by Reference (usable if Box 4b is checked)
   The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. [ ] Microfiche Computer Program *(Appendix)*
7. [ ] Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all necessary)*
   a. [ ] Computer Readable Copy
   b. [ ] Paper Copy (identical to computer copy)
   c. [ ] Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. [X] Assignment Papers (cover sheet & document(s))
9. [ ] 37 CFR 3.73(b) Statement *(when there is an assignee)* [ ] Power of Attorney
10. [ ] English Translation Document *(if applicable)*
11. [ ] Information Disclosure Statement (IDS)/PTO-1449 [X] Copies of IDS Citations
12. [ ] Preliminary Amendment
13. [X] Return Receipt Postcard (MPEP 503) *(Should be specifically itemized)*
14. [ ] Small Entity Statement(s) [ ] Statement filed in prior application, status still proper and desired.
15. [X] Certified Copy of Priority Document(s) *(if foreign priority is claimed)*
16. [ ] Other:

17. If a CONTINUING APPLICATION, *check appropriate box and supply the requisite information:*

[ ] Continuation [ ] Divisional [ ] Continuation-in-part (CIP) of prior application No: ___/_____

18. CORRESPONDENCE ADDRESS

STAAS & HALSEY
Attn: James D. Halsey, Jr.
700 Eleventh Street, N.W., Suite 500
Washington, DC 20001

Telephone: (202) 434-1500
Facsimile: (202) 434-1501

TITLE OF THE INVENTION

Data compressing apparatus, reconstructing apparatus, and its method

BACKGROUND OF THE INVENTION

Field of the invention

The present invention relates to data compressing apparatus, reconstructing apparatus, and its method for forming code data from a character train stream constructed by a structured document including tags. More particularly, the invention relates to data compressing apparatus, reconstructing apparatus, and its method for separating tag information from a character train stream of a structured document and performing a coding and a reconstruction.

Description of the Related Arts

In recent years, various kinds of data such as character codes, image data, and the like is dealt in a computer. Further, in association with the spread of the Internet and Intranet, the numbers of E-mail and electronized documents are increasing. In such a large amount of data, by compressing the data by omitting redundant portions in the data, a storage capacity can be reduced or the compressed data can be sent to a remote place in a short time.

The field of the invention is not limited to the compression of character codes but can be applied to

various data. It is now assumed hereinbelow that the denominations which are used in the information theory, one word unit of data is called a character, and data in which an arbitrary plurality of words are connected is called a character train.

Recently, there is a trend of unifying formats of documents which are handled on computers. In the trend, to efficiently form a document, a method whereby the contents of a document are partially distinguished by using tags, a plurality of document parts such as titles, paragraphs, and the like are preliminarily formed, the relations among the document parts are determined, and the document is structured and edited is tried. As examples of the structured documents such that a concept of a structure is taken in a document, there are structured documents according to the standards of ODA (ISO 8613: Open Document Architecture) and SGML (ISO 8879: Standard Generalized Markup Language) of international standards. As a document processing method using such a structured document, for example, there is a method of JP-A-5-135054. The structured document according to SGML has a high compatibility with a conventional text processing system and has been spread mainly from U.S.A. and put into practical use. In the structured document according to SGML, a template of the document structure is preliminarily given and the document structure is

limited within the template.

Fig. 1 shows a SGML structured document constructed by three portions of SGML declaration 200, document type definition (DTD) 202, and document realization value 204. The template which defines the structure of the document is the document type definition 202. As shown in Fig. 2, the document structure such as chapter, paragraph, title, and the like is defined. In the structured document of SGML, in order to express the document structure, a document text is divided by using an identifier called a tag in the document text.

Fig. 3 shows a specific example of the structured document of SGML. For example, in case of a title of a document, it is expressed by "<TITLE> Specification of the Invention (Device) </TITLE>". That is, characters sandwiched by "<TITLE>" as a start tag and "</TITLE>" as an end tag are elements. In this case, the characters show the title contents "Specification of the Invention (Device)". At present, the number of cases of using SGML is increasing mainly from public organizations. Especially, in U.S.A., the Department of Defense obliges us to submit documents described by SGML. In Japan as well, such a structured document is adopted as a CD-ROM Official Gazette of the Patent Office. HTML (Hyper Text Markup Language) spread as a description form of WWW (World Wide Web) used by the

Internet is one form of SGML.

As a method of compressing a structured document of such SGML or the like, the applicant of the present invention has proposed a method disclosed in Japanese Patent Application Laid-Open No. (JP-A) 9-261072. According to the method, when document data of a structured document having tag information is inputted, the tag information defined by the document type definition DTD or the like is detected. When the tag information is detected, the tag information is outputted as it is without converting. Further, since the tag information is detected, the operating mode is shifted to a mode for coding an input character train except for the tag information.

A basic algorithm of the coding is as shown in Fig. 4. First in step S1, whether an input character or character train is identical to the character or character train preliminarily registered in a dictionary or not is retrieved and compared. If YES, the input data is encoded by a registration number of the dictionary in step S2. In step S3, the code is outputted. When the same registered character or character train cannot be retrieved in step S1, the original input character or character train is outputted as it is in step S5. The above processes are repeated until there is no input character train in step S4. When the SGML document file of Fig. 3 is

subjected to the encoding of Fig. 4, a compression data file of Fig. 5 is obtained. The compression data file has a form in which a portion of the tag information which is not compressed and a portion of a compressed text document mixedly exist in a single file.

According to a method of compressing the document text, since a document text having an enormous data amount can be compressed to a data amount which can be used in practice, this method is a very useful technique to realize an electronized document text. In the compression data file of the structured document as shown in Fig. 5, however, in case of retrieving the tag information in the file, the tag information mixedly exists as a non-compression portion in the compressed document data. The whole file has to be developed into a memory and the necessary tag information has to be retrieved. Even when the user wants to retrieve a keyword in the text as a compressed portion, it is similarly necessary to develop the whole file into the memory and process it. In order to retrieve or obtain the necessary document from the compression data file of the structured document, therefore, it is necessary to read an unnecessary portion as a document, an amount of data to be transmitted increases, it takes time to read the data, and there is a problem such that a large memory area and a large disk capacity need to be assured.

SUMMARY OF THE INVENTION

According to the invention, there is provided a data compressing apparatus for shortening a time to retrieve or read a document and minimizing an increase in capacity of a memory or disk with respect to compression data of a structured document including tag information.

A target of the invention is a data compressing apparatus for forming code data from a character train stream constructed by a document including tags. According to the invention, the data compressing apparatus comprises: a tag information separating unit for separating an identified tag from a character train stream and outputting it as tag information; a tag code replacing unit for arranging a tag code for identification at a position in the character train stream from which the tag was separated by the tag information separating unit; and a character train coding unit for encoding the character train stream including the tag code outputted from the tag code replacing unit and outputting a code stream. According to the data compressing apparatus of the invention, the tag information and the text (character train) in the character train stream of the structured document including the tags are separated and at least the text is encoded, thereby realizing a high compression ratio.

By retrieving the separated tag information, the retrieval can be performed at a high speed. For example, the tag information separated from the text in the compression data file is retrieved and when the coincident tag information can be retrieved, the data is skipped by the data of only the number of data up to the tag information at which the tag code in a reconstructed text has been retrieved, thereby enabling the laser beam to easily reach the head of the target document.

The tag code replacing unit arranges a predetermined fixed code as a tag code at the position in the character train stream from which the tag was separated. By using the fixed code as a tag code, the tag position in the text can be easily retrieved. The tag code replacing unit arranges the tag code indicative of the appearing order of the tags separated by the tag information separating unit at the position in the character train stream from which the tag was separated. By giving the information of the appearing order to the tag code, the retrieval of the text based on the tag information can be performed at a high speed and the reliability can be enhanced. The data compressing apparatus further comprises: a tag information storing unit for storing the tag information separated by the tag information separating unit; a code storing unit for storing code data formed

by the character train coding unit; and a code switching unit for selecting the tag information stored in the tag information storing unit and the code data stored in the code storing unit and outputting the selected tag information or code data. By individually storing the separated tag information and the code data of the text, the retrieval of the compression data and the management for a transfer request can be easily performed.

The character train coding unit comprises: a dictionary storing unit for storing a dictionary in which a character train serving as a processing unit upon compression has been registered; and a character train comparing unit for comparing a partial character train in the character train stream from the tag code replacing unit with the registered character train in the dictionary storing unit to thereby detect the partial character train which coincides with the registered character train, allocating a predetermined code to each of the detected partial character trains, and outputting it. A coring process by the character train coding unit is effective in the compression of document data formed by character codes of a language having a word structure which is not separated by spaces. As a language having the word structure which is not separated by spaces, for example, there are Japanese, Chinese, Hangul, and the like. When

considering Japanese as an example, there is a study result of Japan Electronic Dictionary Research Institute (EDR) Co., Ltd. regarding Japanese words (Yokoi, Kimura, Koizumi, and Miyoshi, "Information structure of electronic dictionary at surface layer level", the papers of Information Processing Society of Japan, Vol. 37, No. 3, pp. 333 - 344, 1996). In the study result, morphemes constructing Japanese, that is, parts of speech of words are added up. When words are simply classified into parts of speech class and the parts of speech class are registered, the number of parts of speech class is equal to 136,486 and they can be expressed by codes of 17 bits (maximum 262,143). The number of characters constructed every word of about 130,000 words constructing a Japanese word dictionary formed by Institute for New Generation Computer Technology (ICOT) is detected and a distribution of the words is obtained. Consequently, it has been found that each of the 70,000 words whose number is more than the half of all of the registered words is constructed by two characters and that the average number of characters is equal to 2.8 characters (44.8 bits). The dictionary storing unit forms and stores a dictionary in which a character train code of a fixed length of, for example, 17 bits is allocated to each word of, for example, about 130,000 words and which is practical as a dictionary of Japanese,

retrieves a registration character train in the dictionary which coincides with the partial character train of the non-compression data, and allocates and outputs the fixed length code of 17 bits as a character train code, thereby enabling the data amount to be substantially compressed to 1/2 or less irrespective of the size of document data.

The data compressing apparatus of the invention has a tag information compressing unit for compressing the tag information separated by the tag information separating unit. The tag information includes a single tag and a combination of a tag and a character train. The tag information compressing unit compresses the tag information in a lump without distinguishing the tag and the character train. An algorithm such as LZ77, LZ78, arithmetic coding, or the like is used to perform the compression. The data compressing apparatus of the invention compresses the tag information by performing the same coding as that of the character train coding unit of the text to a character train of a language such as Japanese or the like which is not separated by spaces in the tag information. That is, the data compressing apparatus of the invention is characterized by comprising: a tag dictionary storing unit for storing a dictionary in which a tag character train in the tag information as a processing unit upon compression has been registered; and a tag character

train comparing unit for comparing a partial character train in a character train stream included in the tag information separated by the tag information separating unit with a registered character in the tag dictionary storing unit to thereby detect the partial character train which coincides with the registered character train, allocating a predetermined code to each of the detected partial character trains, and outputting. By compressing the tag information separated as mentioned above, together with the compression of the text by the character train coding unit, the whole document file can be compressed at a high compression ratio.

The data compressing apparatus of the invention further has a tag position detecting unit for detecting a tag position in code data formed by the character train coding unit. Designation information of the tag position detected by the tag position detecting unit is stored in the tag information storing unit together with the tag information separated by the tag information separating unit. In this case, the tag position detecting unit detects a code amount from the head of a document or a specific tag and stores it together with the tag information into the tag information storing unit. Since a data amount (the number of bytes) from the document head indicative of the position of the corresponding tag code in the compressed text or a specific tag is stored as position

designation information in the separated tag information, if the user wants to retrieve a necessary tag from the tag information, the position of a corresponding tag code in the compression data of the text can be immediately specified and random access of the required text can be efficiently performed.

According to the invention, there is provided a data reconstructing apparatus for reconstructing character train data from a code stream including tag information separated from a character train stream of a document including tags and code data obtained by encoding a character train stream in which a tag code has been arranged at a position of a separated tag.

The data reconstructing apparatus is characterized by comprising: a tag information separating unit for separating tag information and code data from a code stream; a tag information storing unit for storing the tag information separated by the tag information separating unit; and a character train reconstructing unit for reconstructing a character train and a tag code from the code data and, after that, replacing the tag code by the tag information in the tag information storing unit. The character train reconstructing unit executes the operation opposite to that of the character train coding unit and comprises: a dictionary storing unit for storing a dictionary in which a reconstruction character train corresponding to a code

of a character train serving as a processing unit upon reconstruction has been registered; a character train comparing unit for separating the code of the character train as a reconstruction unit from the code stream and reconstructing the original character train by referring to the dictionary storing unit; and a character train replacing unit for replacing the tag code reconstructed by the character train comparing unit by the tag information in the tag information storing unit. If the tag information was compressed by LZ77, LZ78, or the like on the data compressing apparatus side, the data reconstructing apparatus of the invention has a tag information reconstructing unit for reconstructing compression data of the tag information stored in the tag information storing unit. If the character train of the tag information was encoded on the data compressing apparatus side, the data reconstructing apparatus of the invention comprises: a tag dictionary storing unit for storing a dictionary in which a reconstruction character train corresponding to a code of a tag character train serving as a processing unit upon reconstruction has been registered; and a tag character train comparing unit for separating the code of the tag character train as a reconstruction unit from the tag information separated by the tag information separating unit and reconstructing the original tag character train by

referring to the tag dictionary storing unit. The invention further provides a compressing method and a reconstructing method of a structured document including tag information. A data compressing method of forming code data from a character train stream constructed by a document including tags according to the invention comprises:

a tag information separating step of separating a tag identified from a character train stream and outputting it as tag information;

a tag code replacing step of arranging a tag code for identification at a position in the character train stream from which the tag was separated in the tag information separating step; and

a character train coding step of coding the character train stream including the tag code outputted in the tag code replacing step and outputting the code stream.

According to the invention, there is provided a data reconstruction method of reconstructing character train data from a code stream including tag information separated from a character train stream of a document including tags and code data obtained by coding the character train stream in which a tag code has been allocated at a position of the separated tag. The reconstructing method comprises:

a tag information separating step of separating

tag information and code data;

a tag information storing step of storing the tag information separated in the tag information separating step; and

a character train reconstructing step of reconstructing the character train and the tag code from the code data and, after that, replacing the tag information separated in the tag information storing step by the tag code. The details of the data compressing method and the reconstructing method are the same as those in the case of the apparatus.

The above and other objects, features, and advantages of the present invention will become more apparent from the following detailed description with reference to the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an explanatory diagram of a structure of an SGML document;

Fig. 2 is an explanatory diagram of a specific example of a document type definition DTD of the SGML document;

Fig. 3 is an explanatory diagram of an SGML document file with respect to a Japanese document as an example;

Fig. 4 is a flowchart for a fundamental encoding algorithm to compress an SGML document file;

Fig. 5 is an explanatory diagram of an SGML document compression data file in which the portions of non-compressed tag information and the portion of a compressed text mixedly exist;

Fig. 6 is a block diagram of the first embodiment of a data compressing apparatus according to the invention;

Fig. 7 is a block diagram of a tag information separating unit in Fig. 6;

Fig. 8 is an explanatory diagram of a processing procedure of the data compressing apparatus in Fig. 6;

Fig. 9 is an explanatory diagram of a text file in which tags in Fig. 8 are replaced by tag codes;

Fig. 10 is an explanatory diagram of a tag information file separated from a character train stream in Fig. 8;

Fig. 11 is an explanatory diagram of a text file in which the tags in Fig. 8 are replaced by tag codes with an appearing order;

Fig. 12 is a flowchart for a compressing process of the data compressing apparatus in Fig. 6;

Fig. 13 is an explanatory diagram of a research result for a Japanese document;

Fig. 14 is an explanatory diagram of a dictionary structure of a dictionary storing unit in Fig. 6;

Figs. 15A and 15B are flowcharts for an encoding process in Fig. 6 using the dictionary structure in

Fig. 14;

Fig. 16 is a block diagram of the first embodiment of a data reconstructing apparatus of the invention for reconstructing a code stream from the data compressing apparatus in Fig. 6;

Fig. 17 is an explanatory diagram of a dictionary structure of a dictionary storing unit in Fig. 16;

Fig. 18 is a flowchart for a reconstructing process of the data reconstructing apparatus in Fig. 16;

Fig. 19 is a block diagram of the second embodiment of a data compressing apparatus of the invention;

Fig. 20 is a flowchart for a compressing process of the data compressing apparatus in Fig. 19;

Fig. 21 is a block diagram of the third embodiment of a data compressing apparatus of the invention;

Fig. 22 is an explanatory diagram of a processing procedure of the data compressing apparatus in Fig. 21;

Fig. 23 is a block diagram of the second embodiment of a data reconstructing apparatus of the invention for reconstructing a code stream from the data compressing apparatus in Fig. 21;

Fig. 24 is a block diagram of the forth embodiment of the data compressing apparatus of the invention;

Fig. 25 is an explanatory diagram of a processing procedure of the data compressing apparatus in Fig. 24;

Fig. 26 is a flowchart for a data compressing process in Fig. 24;

Fig. 27 is an explanatory diagram of a tag information file and a tag information stream which are stored in the data compressing apparatus in Fig. 24 in which a code amount in Fig. 25 has been added to tags; and

Fig. 28 is a block diagram of the third embodiment of a data reconstructing apparatus of the invention for reconstructing a code stream from the data compressing apparatus in Fig. 24.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 6 is a block diagram of the first embodiment of a data compressing apparatus of the invention. The data compressing apparatus is constructed by a tag information separating unit 10, a tag code replacing unit 12, and a character train coding unit 14. The character train coding unit 14 has a character train comparing unit 16 and a dictionary storing unit 18. The tag information separating unit 10 inputs a character train stream 20 read out from, for example, an SGML Japanese document file shown in Fig. 3, discriminates tags included in the inputted character train stream 20, separates the discriminated tags, and outputs them as a tag information stream 28. The tag code replacing unit 12 arranges a predetermined tag

code at a tag position of the character train stream from which tag information has been separated by the tag information separating unit 10, and supplies a character train stream 22 in which the tag codes have already been arranged to the character train coding unit 14. The character train coding unit 14 encodes the character train stream 22 including the tag codes arranged by the tag code replacing unit 12 and outputs a code stream 26.

Fig. 7 shows the details of the tag information separating unit 10 in Fig. 6 together with the tag code replacing unit 12. The tag information separating unit 10 is constructed by a tag comparing unit 30, a tag identification rule storing unit 32, and an output switching unit 34. An identification rule of the tag information obtained from a document type definition DTD in an SGML document has been stored in the tag identification rule storing unit 32. The tag comparing unit 30 inputs the character train stream 20 and compares it with the identification rule in the tag identification rule storing unit 32. When a comparison output is obtained by the tag information identification, the output switching unit 34 is switched from an output of character train stream 22 to an output of the tag information stream 28, and outputs the identified tag information as a tag information stream 28. At the same time, a comparison result based

on the tag information identification is outputted to the tag code replacing unit 12. A tag code 24 which has been preset in the tag code replacing unit 12 is inserted and arranged from the output switching unit 34 to the position of tag information whose output has been stopped. For example, a hexadecimal fixed code "0x0000" is used as tag information 24 arranged at the position of the tag information of the character train stream 22 by the tag code replacing unit 12.

Fig. 8 is an explanatory diagram of a compressing process according to the data compressing apparatus in Fig. 6 with respect to the character train stream 20 read out from the SGML Japanese document file. An SGML Japanese document file 35 which is inputted as a character train stream 20 for the tag information separating unit 10 is compared with the tag identification rule stored in the tag identification rule storing unit 32 by the tag comparing unit 30 provided in the tag information separating unit 10 in Fig. 7. For example, the head "<TITLE> Specification of the Invention (Device) </TITLE>" is identified as tag information. This tag information is separated like a head position of a tag information file 36. In parallel with the separation of the tag information, a tag code using a hexadecimal fixed code "0x0000" is inserted and arranged to the position where the tag information in the SGML Japanese document file 35 has

been separated. A character train stream of a tag-replaced Japanese document file 38 is formed by replacing the tag information by the tag code. The tag information stream serving as contents of the separated tag information file 36 is outputted as it is. The character train stream serving as contents of the tag-replaced Japanese document file 38 is encoded by the character train coding unit 14 and outputted as a code stream 26.

Fig. 9 shows the tag-replaced Japanese document file 38 obtained by inputting the character train stream 20 of the SGML Japanese document file in Fig. 3 to the data compressing apparatus in Fig. 6 and replacing the tag information by the fixed tag code by the tag code replacing unit 12. In the tag-replaced Japanese document file, the tag information in the SGML Japanese document file in Fig. 3 has been replaced by "(tag code)", respectively.

Fig. 10 shows the tag information file 36 of the tag information separated from the character train stream of the SGML Japanese document file shown in Fig. 3. The tag information included in the inputted character train stream is sequentially separated and stored in the tag information file 36. The tag-replaced character train stream 22 serving as contents of the tag-replaced Japanese document file 38 in Fig. 9 is encoded by the character train coding unit 14 in

Fig. 6 and outputted as a compressed code stream 26.

Fig. 11 shows the tag-replaced Japanese document file 38 when order tag codes showing an appearing order of the tag information are used as tag codes. As order tag codes showing the appearance frequency of the tag information, it is sufficient to use, for example, hexadecimal order tag codes such as "0x001, 0x002, 0x003, ..." which unconditionally correspond in accordance with the appearing order of the tags. In case of using the order tag codes indicative of the appearing order, as shown in Fig. 11, the tag codes themselves replaced in the Japanese character train data indicate the appearing order from the head of the document like "(tag code 1), (tag code 2), (tag code 3), ...". Therefore, when the position of the corresponding tag code in the document file in Fig. 11 is specified by searching the tag information separated as shown in Fig. 10, the searching position in the text can be easily and certainly specified. For example, if the user wants to know the position in the document file of the tag information "<SECTION> Scope of Claim </SECTION>" at line 5 in Fig. 10, since the tag identification information appears at the fifth line from the head, it can be easily specified by searching the position of "(tag code 5)" in which the appearing order is equal to No. 5.

Fig. 12 is a flowchart for a compressing process

by the data compressing apparatus in Fig. 6. First in step S1, the tag information is separated from the character train stream 20 of the input document by the tag information separating unit 10 and outputted. In step S2, the tag code for identification is inserted to the position where the tag exists in the character train stream 20 of the input document by the tag code replacing unit 12. In step S3, the corresponding registration number in the dictionary storing unit 18 is allocated as a code to the character train in the tag-replaced character train stream by the character train comparing unit 16 provided in the character train coding unit 14, and the code stream 26 is outputted. The processes in steps S1 to S3 are repeated until the input of the character train stream is finished in step S4.

The coding process of the tag-replaced character train stream 22 by the character train comparing unit 16 and dictionary storing unit 18 provided in the character train coding unit 14 in Fig. 6 will now be described. The character train comparing unit 16 provided in the character train coding unit 14 in Fig. 6 performs the encoding to allocate a predetermined character train code to each character train constructing a word with reference to the dictionary storing unit 18. First, for example, Japanese document data will now be considered as document data as a

target to be compressed in the character train comparing unit 16. In case of Japanese document data, one character is constructed by word data of two bytes and a word in the document has a structure such that it is not divided by spaces. The Japanese document data is inputted on a unit basis of a document which is used for compression of one time and a document of a proper size on the order of kilobyte to megabyte is inputted. The character train comparing unit 16 sequentially inputs the character trains of the Japanese document data from the head and detects whether they coincide with the registration character trains of a word unit which have previously been registered in the dictionary storing unit 18 or not. When the registration character train which coincides with the input character train is detected in the character train comparing unit 16, the character train code which has previously been registered in correspondence to the coincidence detected registration character train in the dictionary storing unit 18 is read out and allocated. This character train code is outputted.

The dictionary storing unit 18 to convert the character train of the Japanese document data into a character train code on a word unit basis will now be described. Fig. 13 is a sum result regarding parts of speech of morphemes constructing Japanese published by Japan Electronic Dictionary Research Institute (EDR)

Co., Ltd. as a study result. According to the sum result, the number of morphemes corresponding to the number of words is equal to 136,486. When the number of words is expressed by binary numbers, they can be expressed by codes of 17 bits where the maximum number of expression items is equal to 262,143. On the other hand, as a result of obtaining a distribution by detecting the number of characters constructing the words from the Japanese dictionary having about 130,000 words formed by Institute for New Generation Computer Technology (ICOT), each of 70,000 words which are equal to or larger than 1/2 of all of the registered words is constructed by two characters and the average number of characters is equal to 2.8 characters. When the average number of characters (2.8 characters) is expressed by the number of bits, it is equal to

$$2.8 \text{ characters} \times 2 \text{ bytes} = 5.6 \text{ bytes} \times 8 \text{ bits}$$
$$= 44.8 \text{ bits}$$

According to the invention, by executing a coding such that a character train code of 17 bits expressing each of the 136,486 words in Fig. 13 is preliminarily allocated and the character train of the inputted Japanese data is converted to the character train code of 17 bits on a word unit basis, the data amount can be substantially compressed to the half or less.

Fig. 14 shows an embodiment of a dictionary structure of the dictionary storing unit 18 in Fig. 6.

The dictionary stored in the dictionary storing unit 18 in Fig. 6 has a double-layer structure of a head character storing unit 40 and a dependent character train storing unit 42. The head character storing unit 40 uses character codes of Japanese characters "あ、い、う、え、お、 ... (which pronounce a, i, u, e, o, ... in the Roman alphabets)" as indices. Since the Japanese character code is two-byte data, as character codes 44, 131,072 kinds of storing positions from "0x0000" to "0xFFFF" as hexadecimal numbers are allocated. The character code 44 accesses to the position of the corresponding character code by using the head character read by the character train comparing unit 16 in Fig. 6. A head address 46 is stored after the character code 44. When the head character "あ (a)" of the character code 44 is taken as an example, the head address 46 designates a head address "A1" in the dependent character train storing unit 42 in which the dependent character train subsequent to the head character "あ (a)" has been stored. Subsequently, the number of dependent character trains (48) is provided. For example, in case of the head character "あ (a)", (N1 = 4) is stored as the number of dependent character trains (48). In the dependent character train storing unit 42, the head position is designated by the head address 46 stored in correspondence to the character code 44 of the head character in the head character

storing unit 40 and the dependent character trains are stored at the storing positions of the number designated by the dependent character train storing unit 42 from the head position. For example, four storing positions when the number of dependent character trains (48) is (N1 = 4) are designated as dependent character train storing regions as targets from the address A1 of the head address 46 corresponding to the head character "あ (a)". In the dependent character train storing unit 42, a length 50 of dependent character train from the head, a dependent character train 52, and a character train code 54 which is expressed by 17 bits are stored. In the head address A1, for instance, a dependent character train "い (i)" having a length of L1 and its character train code are stored. A dependent character train "う (u)" having a length L2 is stored together with its character train code at the next storing position. In the third region, a dependent character train "お (o)" having a length L3 is stored together with its character train code. In the fourth storing region, a code "NULL" indicating that a dependent character train having a length L4 does not exist is stored and a character train code indicative of the absence is stored. That is, the fourth storing region shows registration of the character train code of only one head character. "あ い う え お か ..楽 闇

鞍 .. 椀 椀 腕" of the head character codes 24 in Fig. 5 and " い う お . . . 件 内 . . . 力 立て 前 . ." of the dependent character trains 32 are examples of Japanese characters each expressed by a 2-byte code and are expressed by the Roman alphabets as " あ (a), い (i), う (u), え (e), お (o), か (ka) ... 案 (an), 闇 (an), 鞍 (an), ..., 椀 (wan), 椀 (wan)" and " い (i), う (u), お (o), ..., 件 (ken), 内 (nai), ..., 力 (chikara), 立て (tate), 前 (mae) ...".

The first to 136,486th character train codes of 17 bits have preliminarily been allocated as character train codes 54 in the dependent character train storing unit 42 in Fig. 14 on the basis of the number of words and the relation between a character train code K and a position address X in case of storing as shown in Fig. 14 can be expressed by the following equation.

$$K = (N \cdot X - A1)/M \quad \ldots (1)$$

where, X: position address in the dependent character train storing unit 42

N: number (1, 2, 3, ..., N) of the dependent character train in which the coincidence has been detected

A1: start address in the dependent character train storing unit

M: storage byte length in the dependent character train storing unit

Since the storage byte length (M) in the dependent character train storing unit 42 is equal to the total length of the length 50 of dependent character train, dependent character train 52, and character train code 54, it can be expressed by, for example, the following equation.

$$\text{Storage byte length } M = \text{length} + \text{character code train} + \text{character train code} \quad \ldots (2)$$

$$= 3 \text{ bits} + 96 \text{ bits} + 17 \text{ bits}$$

$$= 116 \text{ bits}$$

$$= 15 \text{ bytes}$$

A case of allocating 96 bits to the dependent character train 52 by setting the maximum number of characters of the dependent character train which can be stored to six characters is shown here as an example. It will be obviously understood that since the average number of characters of the dependent character train is equal to 2.8 characters, if the maximum number of characters is set to three characters (48 bits) or larger, a sufficient compressing effect can be obtained. In this case, the storage byte length (M) of one storing region in the dependent character train storing unit is equal to 12 bytes. When the character train code (K) of 17 bits which is calculated by the equation (1) is used, it is sufficient to calculate the storing position (address) X from the

value of the character train code (K) by the following equation at the time of reconstruction.

$$X = M \cdot K + A1 \quad \ldots (3)$$

where, K: character train code

A1: start address in the dependent character train storing unit

M: storage byte length in the dependent character train storing unit on the reconstruction side

In the equation (3), since the start address A1 in the dependent character train storing unit 42 in the dictionary which is used on the reconstruction side, that is, an offset and the storage byte length (M) of the dependent character train storing unit 42 have been determined as constants, by substituting the character train code (K) to be reconstructed into the equation (3), the dictionary position (position address) X in which the character train to be reconstructed has been stored can be unconditionally calculated.

Figs. 15A and 15B are flowcharts for the encoding process by the character train comparing unit 16 in Fig. 6 by the dictionary storing unit 18 having the dictionary structure of Fig. 14. First, in step S1, a pointer is moved to a position P of the head character of the character train read to the character train comparing unit 16. A table in the head character

storing unit 40 corresponding to the character code 44 in Fig. 14 shown by the character code at the head character position P is referred to in step S2. With reference to the table in the head character storing unit 40, the head address 46 and the number of dependent character trains (48) in the dependent character train storing unit 42 are obtained in step S3. Subsequently, in step S4, length data L of the length 50 of dependent character train is obtained from the head data in the head address in the dependent character train storing unit 42. In step S5, L characters based on the length data L of the dependent character train are extracted from the head character position P, the extracted L characters are compared with the registration character train of the dependent character train 52 in the dependent character train storing unit 42, thereby discriminating whether they coincide or not. When the extracted L characters coincide with the registered dependent character train, the processing routine advances to step S8, the next character train code 54 is read out and is allocated to the coincidence detected character train by the character train comparing unit 16, and the resultant character train is outputted. In step S9, the pointer at the head character position P is updated to the position P where it is moved by only the number L of characters of the dependent character train. If a

process for non-compression data is not finished in step S12, the processing routine is again returned to step S2 and similar processes are repeated with respect to the updated head character position P. On the other hand, when the extracted character does not coincide with the registration dependent character train in the dependent character train storing unit 42 in step S5, a check is made to see whether the process to the number (N) of dependent character trains has been finished or not. If it is not finished yet, the processing routine is returned to step S7. The length data L of the dependent character train is obtained from the next storing region in the head address in the dependent character train storing unit 42. The dependent character train of the L characters is extracted again from the head character position P in step S5 and is compared with the registration dependent character train in the dependent character train storing unit 42 to see whether they coincide or not. In a case where they do not coincide even when the comparing process is performed with respect to all of the dependent character trains of the registration number (N) by repetition of steps S5 to S7, the end of the number (N) of dependent character trains is discriminated in step S6. The processing routine advances to step S10 and a non-registered code indicative of one character of the head character is transmitted. In step S11, the

pointer is updated to a next position where the head character position P has been moved only by the number (L) of characters (L = 1). The processing routine is returned from step S12 to step S2 and the processes from the next head character position P are repeated.

Fig. 16 is a block diagram of the first embodiment of a data reconstructing apparatus for reconstructing a character train stream from the code stream which is outputted from the data compressing apparatus in Fig. 6 and constructed by the code stream 26 and tag information stream 28. The data reconstructing apparatus comprises a tag information separating unit 60, a tag information storing unit 62, and a character train reconstructing unit 64. The character train reconstructing unit 64 has a code train comparing unit 66, a dictionary storing unit 65, and a character train replacing unit 68. The tag information separating unit 60 inputs a code stream 56 sent from the data compressing apparatus side in Fig. 6 and separates it into the tag information and the code data. The tag information is stored into the tag information storing unit 62. The code data is outputted as a code stream 56 to the character train reconstructing unit 64. The character train reconstructing unit 64 reconstructs the character train and the tag code from the code data in the code train comparing unit 66 by using the dictionary storing unit 65. After that, in the

character train replacing unit 68, the tag code is replaced by the tag information stored in the tag information storing unit 62 and a reconstructed character train stream 70 is outputted.

Fig. 17 is a flowchart for the reconstructing process of the data reconstructing apparatus in Fig. 16. First in step S1, the tag information separating unit 60 separates the tag information from the code stream 56 corresponding to the input document and stores it into the tag information storing unit 62. In step S2, the code train in the code stream 56 from which the tag information has been separated is compared and collated with the registration number in the dictionary storing unit 65 and converted into the character or character train stored by the coincident registration number. In step S3, the tag codes included in the reconstructed character train are sequentially replaced in accordance with the storing order of the tag information stored in the tag information storing unit 62 and outputted as a reconstructed character train stream 70. The processes in steps S1 to S3 are repeated until the input of the code stream 56 is finished in step S4. With reference to the dictionary storing unit 65, the code train comparing unit 66 provided in the character train reconstructing unit 64 in Fig. 16 reconstructs the original character train from the code train stream

encoded by the data compressing apparatus in Fig. 6.

Fig. 18 shows a dictionary structure of the character train dictionary storing unit 65 in Fig. 16. In the character train dictionary storing unit 65, a head character 72, a dependent character train length 74, and a dependent character train 76 have been stored in accordance with the order of the character train code 54 of 17 bits in the dependent character train storing unit 42 shown in the dictionary structure in Fig. 14. Therefore, in the code train comparing unit 66, since the storage byte length M of the dependent character train storing unit 42 which is used for reconstruction has been known from

storage byte length M = head character + length
+ character code train
= 16 bits + 3 bits + 96 bits
= 115 bits
= 15 bytes, ... (6)

the position address X corresponding to the character train code K can be calculated from the following equation.

$$X = M \cdot K + A1 \quad \ldots (7)$$

where, K: character train code
A1: start address of character train storing position

M: storage byte length

By obtaining and referring to the position address X showing the dictionary storing position from the separated character train code K as mentioned above, the character train comprising a combination of the corresponding head character and dependent character train can be reconstructed.

By the data compressing apparatus of Fig. 6 and the data reconstructing apparatus of Fig. 16 as mentioned above, the character train stream of the SGML Japanese document file shown in Fig. 3 is separated into the tag information as shown in Fig. 10 and the character train stream in which the tag information is replaced by the tag code as shown in Fig. 9. In the embodiment, by encoding the character train stream which has already been replaced to the tag code, the portion corresponding to the text of the document file can be converted into a compression file of a high compression ratio. The tag information separated as shown in Fig. 10 is retrieved by using a keyword and if the tag information which coincides with the keyword is obtained, to which number the appearing position of the tag information corresponds is detected. Thus, by retrieving the appearing position of the tag code included in the document file of the tag code-replaced text in Fig. 9, the reading operation by specifying the

document position corresponding to the retrieval result of the tag information or the like can be easily performed.

Fig. 19 shows the second embodiment of a data compressing apparatus of the invention. The embodiment is characterized by providing a tag information storing unit 78 and a code storing unit 80 in addition to the first embodiment of Fig. 6. The tag information separated from the character train stream 20 by the tag information separating unit 10 is stored into the tag information storing unit 78. Thus, for example, the tag information file 36 as shown in Fig. 10 is stored into the tag information storing unit 78. The code storing unit 80 is provided in the character train coding unit 14. The code data formed by the coding process in Fig. 15 is stored into the code storing unit 80 with respect to the tag-replaced character train stream 22 obtained by inserting the tag information into the tag information separated by the tag code replacing unit 12. Besides the tag information storing unit 78 and code storing unit 80, a code switching unit 82 is provided at the output stage. The code switching unit 82, for example, sequentially selects the tag information stored in the tag information storing unit 78 and the code data stored in the code storing unit 80 and outputs them as a code train stream 84.

Fig. 20 is a flowchart for a compressing process

of the data compressing apparatus of Fig. 19. In the compressing process, in step S1, the tag information is separated from the character train steam 20 of the input document by the tag information separating unit 10 and stored into the tag information storing unit 78. In step S2, a tag code for identification is inserted to a position where the tag exists in the character train stream 20 by the tag code replacing unit 12. In step S3, the character train of the character train stream 22 after completion of the replacement of the tag code is inputted to the character train comparing unit 16 of the character train coding unit 14 and converted into the corresponding registration number of the dictionary structure in the dictionary storing unit 18. The processes in steps S1 to S3 as mentioned above are repeated until the input of the character train stream is finished in step S4. When the input of the character train stream is finished, step S5 follows. The code streams encoded by converting into the separated tag information and tag code are sequentially read out from, for example, the tag information storing unit 78 and code storing unit 80 and outputted as a code train stream 84. By inputting the code train stream 84 outputted from the data compressing apparatus in Fig. 19 to the data reconstructing apparatus shown in Fig. 16, the character train stream can be reconstructed.

Fig. 21 shows the third embodiment of a data compressing apparatus of the invention. The embodiment is characterized in that the tag information separated from the character train stream is compressed. In the data compressing apparatus, a tag information compressing unit 86 is newly provided between the tag information separating unit 10 and tag information storing unit 78 in the second embodiment in Fig. 19. The tag information compressing unit 86 compresses the tag information inputted and separated from the character train stream 20 by the tag information separating unit 10 as a character train stream as a target of the compression and stores it into the tag information storing unit 78. As for the compressing process by the tag information compressing unit 86, a compression algorithm such as LZ77, LZ78, arithmetic encoding, or the like is used since the tags and the Japanese character train are included in the tag information and they are compressed in a lump. The tag information separating unit 10, tag code replacing unit 12, and character train coding unit 14 are the same as those in the second embodiment of Fig. 19. Fig. 22 is an explanatory diagram of the compressing process by the data compressing apparatus of Fig. 21. The character train stream 20 serving as contents of the SGML Japanese document file 35 is separated into the tag information serving as contents of the tag

information file 36 by the tag information separating unit 10. After the tag information was compressed by the tag information compressing unit 86, it is outputted via the storage of the tag information storing unit 78. A fixed tag code or an order tag code indicative of the appearing order is inserted and arranged by the tag code replacing unit 12 to the position of the tag information separated from the character train stream 20 serving as contents of the SGML Japanese document file 35. The character train stream 22 serving as contents of the tag-replaced Japanese document file 38 is outputted to the character train coding unit 14. The code data compressed by the character train encoding is outputted via the storage by the code storing unit 80.

Fig. 23 shows the second embodiment of a data reconstructing apparatus of the invention for reconstructing a character train stream from a code stream 90 outputted from the data compressing apparatus in Fig. 21. The data reconstructing apparatus further has a compression tag storing unit 92 and a tag information reconstructing unit 94 in addition to the first embodiment of Fig. 16. The tag information separating unit 60 separates the compression tag information included in the code stream 90 which is inputted and stores the separated compression tag information into the compression tag storing unit 92.

The compression tag information stored in the compression tag storing unit 92 is reconstructed by the tag information reconstructing unit 94 and stored into the tag information storing unit 62. The tag information reconstructing unit 94 executes a reconstruction algorithm corresponding to LZ77, LZ78, or arithmetic decoding on the data compression side. The other construction is substantially the same as that in Fig. 19.

Fig. 24 shows the fourth embodiment of a data compressing apparatus of the invention. The embodiment is characterized in that the Japanese character train in the separated tag information is compressed by encoding and, further, position designation information indicative of the position of the replaced tag code in the text is added to the separated tag information. In the fourth embodiment, the tag information separating unit 10, the tag code replacing unit 12, the character train coding unit 14 having the character train comparing unit 16 and dictionary storing unit 18, the tag information storing unit 78, and the code switching unit 82 are substantially the same as those in the second embodiment of Fig. 19. Besides them, a tag character train comparing unit 97, a tag dictionary storing unit 96, and a code amount measuring unit 98 are newly provided. In the tag character train comparing unit 97 and tag dictionary storing unit 96,

the Japanese character train stream included in the tag information separated by the tag information separating unit 10 is encoded by a coding algorithm similar to that in the character train coding unit 14, thereby compressing the tag information. Therefore, a dictionary structure in the tag information storing unit 78 is the same as that in Fig. 14 and the Japanese character train which is used in the tag information is used as a head character and dependent characters. The coding process of the tag character train is performed in accordance with the flowcharts of Figs. 15A and 15B. The code amount measuring unit 98 provided in the data compressing apparatus measures a code amount in a range from the head of the character train stream to each replaced tag code with respect to the code data due to the encoding with regard to the character train stream 22 of the text by the character train coding unit 14, namely, the character train stream 22 in which the replacement of the tag code was finished as a target. The code amount measuring unit 98 adds a measurement result of the code amount to each tag code as code position information to each of the tag information separated from the character train stream to be stored into the tag information storing unit 78 and stores it. As position designation information indicative of the position of the tag information replaced by the tag code by the code amount measuring unit 98, besides the

code amount from the head of the character train stream, a code amount of the code data in a range from specific tag information in the character train stream to each subsequent tag information can be used.

Fig. 25 is an explanatory diagram of a compressing process in the fourth embodiment of Fig. 24. The processes such that the character train stream serving as contents of the SGML Japanese document file 35 is inputted, the tag information file 36 by the separation of the tag information is formed, and the tag-replaced Japanese document file 38 in which the tag information was replaced by the tag code is formed are substantially the same as those in the second embodiment of Fig. 19. Besides them, a tag character train as a Japanese character train included in the tag information in the separated tag information file 36 is encoded and compressed by using the tag dictionary storing unit 96, thereby outputting.

Fig. 26 shows a specific example of the tag information file stored in the tag information storing unit 78 and relates to the tag information, as an example, separated from the SGML Japanese document file shown in Fig. 3. Code amounts (byte amounts) DL1 to DL13 from the head of the code data of the character train data in the tag-replaced Japanese file 38 in Fig. 25 have been stored as position designation information 106 on the right side in the tag information file 36 in

correspondence to each tag corresponding to indices 01 to 13 on the left side, respectively.

Fig. 27 is a flowchart for the compressing process according to the fourth embodiment of Fig. 24. First, steps S1 to S4 are the same as those in Fig. 12. The tag information separated from the character train stream 20 by the tag information separating unit 10 is stored into the tag information storing unit 78. The character train stream 22 in which the tag code 24 has been inserted and arranged to the position of the tag information separated by the tag code replacing unit 12 is encoded by the character train coding unit 14. The code data is stored into the code storing unit 80. In step S4, when the replaced tag code is encoded by the character train coding unit 14, the code amount measuring unit 98 measures, for example, a code amount DL from the head of the character train stream. The measured code amount DL is stored as position designation information 106 in Fig. 26 into the tag information already stored in the tag information storing unit 78. The processes in steps S1 to S4 are repeated until the input of the character train stream is finished in step S5. When the input of the character train stream 20 is finished, in step S6, the coding process for converting the character train in the tag information separated and stored in the tag information storing unit 78 into the corresponding

block number of the dictionary in the tag dictionary storing unit 96 and using it as code data is executed by the tag character train comparing unit 97. The resultant data is stored into the tag information storing unit 78. Thus, the contents stored in the tag information storing unit 78 are as shown in the compression tag information file 36 in Fig. 26. In step S7, finally, the tag information with the code amount which was separated and encoded by the tag information storing unit 78 and the code data stored in the code storing unit 80 are, for example, sequentially selected and outputted by the code switching unit 82 and supplied as a code stream 100 to the outside. In the compressing process in Fig. 27, the separation and replacement of the tag information in steps S1 to S4, and further, the measuring process of the amount of compressed codes and the subsequent coding process of the separated tag information are time-divisionally performed. However, both of them can be processed in parallel.

Fig. 28 shows the third embodiment of a data reconstructing apparatus of the invention for reconstructing a character train stream from the code stream 100 outputted from the data compressing apparatus in Fig. 24. In the embodiment, the tag information separating unit 60, compression tag storing unit 92, tag information storing unit 62, and character

train reconstructing unit 64 are substantially the same as those in the second embodiment in Fig. 23. Besides them, a tag character train reconstructing unit 102 and a tag reconstruction dictionary storing unit 104 are newly provided. As a tag reconstruction dictionary storing unit 104, the unit having the same dictionary structure as that in Fig. 17 is used and the stored characters become the Japanese character train which is used in the tags. The tag information separating unit 60 separates the tag information stream as shown in the contents of the compression tag information file 36 in Fig. 26 from the code stream 100 which is supplied from the data compressing apparatus side in Fig. 24 and stores it into the compression tag storing unit 92. The compression tag information stored in the compression tag storing unit 92 is reconstructed to the corresponding Japanese character train with reference to the dictionary number by the code of the tag character train in the tag reconstruction dictionary storing unit 104 by the tag character train reconstructing unit 102. The tag information including the reconstructed Japanese character train is stored into the tag information storing unit 62. The tag information separating unit 60 supplies the code stream of the document text that is sent after the compression tag information stream to the character train reconstructing unit 64. In the code train comparing

unit 66, the corresponding characters or character train is reconstructed with reference to the dictionary number in the dictionary storing unit 65 by the extracted code and outputted to the character train replacing unit 68. The character train replacing unit 68 recognizes the tag code in the reconstructed character train, sequentially extracts the reconstructed tag information stored in the tag information storing unit 62 in accordance with the appearing order, replaces it by the tag code, and outputs the reconstructed character train stream. As shown in Fig. 26, the compression tag information file 36 has been stored in the compression tag storing unit 92 at a time point when the input of the compression tag information stream separated from the code stream 100 is finished. Therefore, the compression tag information file 36 is retrieved by using a specific tag as a keyword. If the coincident tag is obtained, the code amount DL as position designation information corresponding thereto is read out. It is possible to request the data compressing apparatus of Fig. 24 to transfer the code data from the position of the retrieved code amount DL. Thus, by transferring the partial compression text data of the SGML Japanese document which is necessary from the data reconstructing side to the data compressing side, the data can be easily read.

As mentioned above, according to the invention, with respect to the character train stream of the structured document such as SGML or the like including the tags, a high compression ratio is realized by separating the tag information and the text (character train) and encoding at least the text. By retrieving the separated tag information, the reading and the retrieval of the specific tag position in the compressed code data can be processed at a high speed. That is, the order of the separated tag information and that of the tag codes replaced in the code data correspond in a one-to-one correspondence relation. By retrieving the specific tag information with respect to the tag information, the position of the tag code in the code data can be specified by such orders. It is possible to easily reach the head position of the target document code data. Thus, with respect to the structured document such as an SGML including the tags, the compression and reconstruction can be performed at a high speed while maintaining a high compression ratio.

As a transmitting form from the data compressing apparatus to the data reconstructing apparatus in the invention, a communication line such as Internet or the like or a proper form of a rewritable portable medium such as optical disk cartridge, magnetic disk cartridge, or the like can be used. In the foregoing

embodiments, as a compression of the character train stream in which the tag information is separated and the tag code is replaced to the position of the separated tag information, the encoding in which the character train code of a fixed length corresponding to the number of words peculiar to Japanese is allocated is performed as an example. However, it will be obviously understood that the compression by LZ77, LZ78, arithmetic encoding, or the like other than the above method can be performed. Further, the invention is not limited by the numerical values in the foregoing embodiments. Further, the invention incorporates many modifications and variations within the purview of the invention without departing from the objects and advantages thereof.

WHAT IS CLAIMED IS:

1. A data compressing apparatus for generating code data from a character train stream constructed by a document including tags, comprising:

a tag information separating unit for separating the identified tag from said character train stream and outputting as tag information;

a tag code replacing unit for arranging a tag code for identification to a position of the character train stream in which the tag was separated by said tag information separating unit; and

a character train coding unit for coding the character train stream including the tag code outputted from said tag code replacing unit and outputting a code stream.

2. An apparatus according to claim 1, wherein said tag code replacing unit arranges a predetermined fixed code as said tag code to the position of the character train stream in which the tag was separated.

3. An apparatus according to claim 1, wherein said tag code replacing unit arranges a tag code indicative of an appearing order of the tag separated by said tag information separating unit to the position of the character train stream in which the tag was separated.

4. An apparatus according to claim 1, further comprising:

a tag information storing unit for storing the tag information separated by said tag information separating unit;

a code storing unit for storing the code data formed by said character train coding unit; and

a code switching unit for selecting the tag information stored in said tag information storing unit and the code data stored in said code storing unit and outputting the selected tag information or code data.

5. An apparatus according to claim 1, wherein said character train coding unit comprises:

a dictionary storing unit for storing a dictionary in which a character train serving as a processing unit when compressing has been registered; and

a character train comparing unit for comparing a partial character train in the character train stream from said tag code replacing unit with the registration character train in said dictionary storing unit, thereby detecting a partial character train which coincides with said registration character train, allocating a predetermined code every said detected partial character train, and outputting a resultant character train.

6. An apparatus according to claim 1, further comprising a tag information compressing unit for compressing the tag information separated by said tag information separating unit.

7. An apparatus according to claim 1, further comprising:

a tag dictionary storing unit for storing a dictionary in which a tag character train in the tag information serving as a processing unit when compressing has been registered; and

a tag character train comparing unit for comparing the partial character train of the character train stream included in the tag information separated by said tag information separating unit with the registration character train in said tag dictionary storing unit, thereby detecting a partial character train which coincides with said registration character train, allocating a predetermined code every said detected partial character train, and outputting a resultant character train.

8. An apparatus according to claim 4, further comprising a tag position detecting unit for detecting a position of the tag in the code data formed by said character train coding unit,

and wherein both the tag information separated by

said tag information separating unit and designation information of the tag position detected by said tag position detecting unit are stored in said tag information storing unit.

9. An apparatus according to claim 8, wherein said tag position detecting unit detects the code amount from the head of a document or a specific tag and stores it together with the tag information into said tag information storing unit.

10. A data reconstructing apparatus for reconstructing character train data from a code stream including tag information separated from a character train stream of a document including tags and code data obtained by encoding a character train stream in which a tag code has been arranged at a position of the separated tag, comprising:

a tag information separating unit for separating said tag information and said code data from said code stream;

a tag information storing unit for storing the tag information separated by said tag information separating unit; and

a character train reconstructing unit for reconstructing the character train data including the character train and the tag code from said code data

and, thereafter, replacing said tag code by the tag information in said tag information storing unit.

11. An apparatus according to claim 10, wherein said character train reconstructing unit comprises:

a dictionary storing unit for storing a dictionary in which a reconstruction character train corresponding to a code of the character train serving as a processing unit when reconstructing has been registered;

a character train comparing unit for separating a code of the character train serving as a reconstruction unit from said code stream and reconstructing the original character train with reference to said dictionary storing unit; and

a character train replacing unit for replacing the tag code reconstructed by said character train comparing unit by the tag information in said tag information storing unit.

12. An apparatus according to claim 10, further comprising a tag information reconstructing unit for reconstructing compression data of the tag information stored in said tag information storing unit.

13. An apparatus according to claim 10, further comprising:

a tag dictionary storing unit for storing a dictionary in which a reconstruction character train corresponding to a code of a tag character train serving as a processing unit when reconstructing has been registered; and

a tag character train comparing unit for separating a code of the tag character train serving as a reconstruction unit from the tag information separated by said tag information separating unit and reconstructing the original tag character train with reference to said dictionary storing unit.

14. A data compressing method of generating code data from a character train stream constructed by a document including tags, comprising:

a tag information separating step of separating the identified tag from said character train stream and outputting as tag information;

a tag code replacing step of arranging a tag code for identification to a position of the character train stream in which the tag was separated in said tag information separating step; and

a character train coding step of coding the character train stream including the tag code outputted from said tag code replacing step and outputting a code stream.

ABSTRACT OF THE DISCLOSURE

A tag information separating unit separates a tag identified from a character train stream and outputs as tag information. A tag code replacing unit arranges a tag code for identification to a position of the character train stream in which the tag was separated. A character train coding unit compression encodes the character train stream including a tag code which is outputted from the tag code replacing unit. A data reconstructing apparatus reconstructs the character train stream by the operation opposite to the compression.

FIG. 1 PRIOR ART



FIG. 2 PRIOR ART

```
                    .........
<!--=========Link Markup ======================-->
<!ENTITY % linkType "NAMES">
<!ENTITY % linkExtraAttributes
        "REL %linkType#IMPLIED
        REV %linkType#IMPLIED
        URN CDATA#IMPLIED
        TITLE CDATA#IMPLIED
        METHODS NAMES#IMPLIED
        ">
<![% HTML.Recommended [
        <!ENTITY % A.content  "(%text)* "
        --<H1><a name="xxx">Heading</a></H1>
                is preferred to
            <a name="xxx"></H1>Heading</H1></a>
        -->
]]>
<!ENTITY % A.content  "(%heading | %text)* ">
<!ELEMENT A       --%A.content-(A)>
<!ATTLIST A
        HREF CDATA#IMPLIED
        NAME CDATA#IMPLIED
        %linkExtraAttributes;
        %SDAPREF;"<Anchor:#AttList>"
<!--<A>            Anchor;source/destination of link   -->
<!--<A NAME="...">   Name of this anchor                 -->
<!--<A HREF="...">   Address of link destination        -->
<!--<A URN="...">   Permanent address of destination    -->
                    .........
```

FIG. 3

<TITLE>SPECIFICATION OF THE INVENTION (DEVICE) </TITLE>
<SECTION>TITLE OF THE INVENTION (DEVICE) </SECTION>
DATA COMPRESSING·RECONSTRUCTING METHOD AND APPARATUS AND DOCUMENT MANAGEMENT SYSTEM<P>
<SECTION>SCOPE OF CLAIM</SECTION>
<SUBSECTION>A DATA COMPRESSING APPARATUS FOR ENCODING INPUT DATA,
</SUBSECTION>
<LIST>
<ITEM>MEANS FOR HOLDING A CODE TABLE
<ITEM>STEP OF ENCODING INPUT DATA ON THE BASIS OF A CODE TABLE
</LIST>A DATA COMPRESSING METHOD CHARACTERIZED BY COMPRISING:<P>
<SECTION>DETAILED DESCRIPTION OF THE INVENTION</SECTION>
<SUBSECTION>INDUSTRIAL FIELD OF UTILIZATION</SUBSECTION>
<PARAGRAPH>IN RECENT YEARS, VARIOUS KINDS OF DATA SUCH AS CHARACTER CODES, VECTOR INFORMATION, AND IMAGES HAS BEEN HANDLED BY A COMPUTER AND AN AMOUNT OF DATA WHICH IS HANDLED IS ALSO RAPIDLY INCREASING. WHEN A LARGE AMOUNT OF DATA IS HANDLED, BY COMPRESSING THE DATA AMOUNT BY OMITTING REDUNDANT PORTIONS IN THE DATA, A MEMORY CAPACITY CAN BE REDUCED AND THE DATA CAN BE TRANSMITTED AT A HIGH SPEED.
<PARAGRAPH>RECENTLY, THERE IS A TREND OF UNIFYING FORMATS OF DOCUMENTS WHICH ARE HANDLED BY COMPUTERS. THE FORMATS OF DOCUMENTS WHICH WERE DIFFERENT FOR COMPUTERS OR APPLICATIONS SO FAR ARE ENABLED TO BE USED EVEN BY DIFFERENT COMPUTERS. <TT>SGML (STANDARD GENERALIZED MARKUP LANGUAGE) </TT>IN 1986, IS

FIG. 4



FIG. 5

<TITLE>SPECIFICATION OF THE INVENTION(DEVICE)</TITLE><P>
<SECTION>TITLE OF THE INVENTION(DEVICE)</SECTION>
275fe5a1d8... (COMPRESSION AREA) ... 6efc312903
<SECTION>SCOPE OF CLAIM</SECTION>
<SUBSECTION>A DATA COMPRESSING APPARATUS FOR ENCODING INPUT DATA,
</SUBSECTION>
6ef208ca9d... (COMPRESSION AREA) ... 358eac0e66f8
<SECTION>DETAILED DESCRIPTION OF THE INVENTION</SECTION>
<SUBSECTION>INDUSTRIAL FIELD OF UTILIZATION</SUBSECTION>
398ecad978... (COMPRESSION AREA) ... ffd938e06b

FIG. 6



FIG. 7


CHARACTER TRAIN STREAM 20
10
OUTPUT SWITCHING UNIT 34
TAG COMPARING UNIT 30
TAG IDENTIFICATION RULE STORING UNIT 32
TAG CODE REPLACING UNIT 12
TAG CODE 24
TAG INFORMATION STREAM 28
TAG-REPLACED CHARACTER TRAIN STREAM 22

FIG. 8


SGML JAPANESE DOCUMENT FILE 35
<TITLE> SPECIFICATION OF THE INVENTION (DEVICE) </TITLE> <P>
<SECTION> TITLE OF THE INVENTION (DEVICE) </SECTION>
DATA COMPRESSING·RECONSTRUCTING METHOD AND APPARATUS AND DOCUMENT MANAGEMENT SYSTEM <P>
SEPARATE
REPLACE
TAG INFORMATION FILE 36
TAG-REPLACED JAPANESE DOCUMENT FILE 38
01
02
03
<TITLE> SPECIFICATION OF THE INVENTION (DEVICE) </TITLE> <P>
<SECTION> TITLE OF THE INVENTION (DEVICE) </SECTION>
<P>
(TAG CODE) (TAG CODE)
(TAG CODE)
DATA COMPRESSING·RECONSTRUCTING METHOD AND APPARATUS AND DOCUMENT MANAGEMENT SYSTEM (TAG CODE)
ENCODE CHARACTER TRAIN
OUTPUT
OUTPUT

FIG. 9



FIG. 10



FIG. 11



FIG. 12


START
S1
SEPARATE TAG INFORMATION FROM CHARACTER TRAIN STREAM IN INPUT DOCUMENT AND OUTPUT
S2
INSERT TAG CODE TO POSITION WHERE THERE IS A TAG IN CHARACTER TRAIN STREAM
S3
ALLOCATE CHARACTER TRAIN IN CHARACTER TRAIN STREAM TO CORRESPONDING REGISTRATION NO. IN DICTIONARY STORING UNIT
S4
INPUT IS FINISHED ?
NO
YES
END

FIG. 13

PART OF SPEECH CLASS	THE NUMBER OF MORPHEMES (THE TOTAL NEMBER)	COMPONENT RATIO (%)	THE NUMBER OF MORPHEMES (THE DIFFERENT NUMBER)	COMPONENT RATIO (%)
NOUN CLASS	1, 375, 378	26. 1	110, 912	81. 3
VERB CLASS	622, 125	11. 8	14, 638	10. 7
ADJECTIVE CLASS	58, 742	1. 1	1, 204	0. 9
ADJECTIVE VERB CLASS	61, 192	1. 2	3, 796	2. 8
ADVERB CLASS	74, 332	1. 4	2, 934	2. 1
PARTICIPIAL ADJECTIVE CLASS	40, 271	0. 8	247	0. 2
CONJUNCTION CLASS	23, 562	0. 4	247	0. 2
PREFIX CLASS	21, 063	0. 4	318	0. 2
SUFFIX CLASS	122, 954	2. 3	1, 330	1. 0
WORDS' ENDING CLASS	631, 304	12. 0	155	0. 1
POST POSITIONAL WORD CLASS	1, 402, 757	26. 7	171	0. 1
AUXILIARY VERB CLASS	319, 852	6. 1	203	0. 1
INTERJECTION CLASS	356	0. 0	105	0. 1
OTHERS	508, 333	9. 7	226	0. 2
TOTAL	5, 262, 221	100. 0	136, 486	100. 0

FIG. 14


18
HEAD CHARACTER STORING UNIT 40
DEPENDENT CHARACTER TRAIN STORING UNIT 42
44
46
48
50
52
54
THE ORDER OF CHARACTER CODES
あ
い
う
え
お
か
案
闇
鞍
湾
碗
腕
HEAD ADDRESS A1
HEAD ADDRESS A2
HEAD ADDRESS A3
HEAD ADDRESS A4
HEAD ADDRESS A5
HEAD ADDRESS A6
HEAD ADDRESS Ac
HEAD ADDRESS Ad
HEAD ADDRESS Ae
HEAD ADDRESS Ag
HEAD ADDRESS Ah
HEAD ADDRESS Ai
THE NUMBER N1
THE NUMBER N2
THE NUMBER N3
THE NUMBER N1
THE NUMBER N2
THE NUMBER N3
THE NUMBER Nc
THE NUMBER Nd
THE NUMBER Ne
THE NUMBER Ng
THE NUMBER Nh
THE NUMBER Ni
LENGTH L1
LENGTH L2
LENGTH L3
LENGTH L4
LENGTH Lq
LENGTH Lr
LENGTH Ls
LENGTH Lw
LENGTH Lx
LENGTH Ly
LENGTH Lz
い
う
お
NULL
件
内
NULL
力
立て
前
NULL
CHARACTER TRAIN CODE

FIG. 15A


START
S1
MOVE POINTER TO HEAD CHARACTER POSITION P
S2
REFER TO HEAD CHARACTER TABLE IN STATIC DICTIONARY SHOWN BY CHARACTER CODE AT POSITION P
S3
OBTAIN HEAD ADDRESS A AND THE NUMBER N IN DEPENDENT CHARACTER TABLE FROM HEAD CHARACTER TABLE
S4
OBTAIN LENGTH DATA L FROM HEAD DATA IN ADDRESS A
S5
L CHARACTER FROM POSITION P COINCIDES WITH DEPENDENT CHARACTER TRAIN?
YES
NO
S6
PROCESSES FOR THE NUMBER N ARE NOT FINISHED ?
YES
NO
S7
OBTAIN LENGTH DATA L FROM NEXT DATA OF ADDRESS A

FIG. 15B



FIG. 16


CODE STREAM 56
TAG INFORMATION SEPARATING UNIT 60
TAG INFORMATION STORING UNIT 62
64
CODE TRAIN COMPARING UNIT 66
DICTIONARY STORING UNIT 65
CHARACTER TRAIN REPLACING UNIT 68
CHARACTER TRAIN STREAM 70
TAG INFORMATION

FIG. 17



FIG. 18


65
72
74
76
HEAD CHARACTER
LENGTH L1
い
HEAD CHARACTER
LENGTH L2
う
HEAD CHARACTER
LENGTH L3
お
HEAD CHARACTER
LENGTH L4
NULL
HEAD CHARACTER
LENGTH Lq
件
HEAD CHARACTER
LENGTH Lr
内
HEAD CHARACTER
LENGTH Ls
NULL
HEAD CHARACTER
LENGTH Lw
力
HEAD CHARACTER
LENGTH Lx
立て
HEAD CHARACTER
LENGTH Ly
前
HEAD CHARACTER
LENGTH Lz
NULL
CHARACTER TRAIN REGISTRATION ADDRESS X

FIG. 19


CHARACTER TRAIN STREAM 20
TAG INFORMATION STORING UNIT 78
TAG INFORMATION SEPARATING UNIT 10
TAG CODE REPLACING UNIT 12
TAG CODE 24
22
TAG INFORMATION STREAM 28
CHARACTER TRAIN COMPARING UNIT 16
DICTIONARY STORING UNIT 18
14
CODE STORING UNIT 80
26
CODE SWITCHING UNIT 82
CODE TRAIN STREAM 84

FIG. 20



FIG. 21


CHARACTER TRAIN STREAM 20
TAG INFORMATION SEPARATING UNIT 10
TAG INFORMATION COMPRESSING UNIT 86
TAG CODE REPLACING UNIT 12
24
22
CHARACTER TRAIN COMPARING UNIT 16
DICTIONARY STORING UNIT 18
14
CODE STORING UNIT 80
TAG INFORMATION STORING UNIT 78
COMPRESSION TAG INFORMATION STREAM 88
CODE SWITCHING UNIT 82
CODE STREAM 90

FIG. 22


35
<TITLE> SPECIFICATION OF THE INVENTION (DEVICE) </TITLE> <P>
<SECTION> TITLE OF THE INVENTION (DEVICE) </SECTION>
DATA COMPRESSING·RECONSTRUCTING METHOD AND APPARATUS AND DOCUMENT MANAGEMENT SYSTEM <P>
SEPARATE
REPLACE
36
38
01 <TITLE> SPECIFICATION OF THE INVENTION (DEVICE) </TITLE> <P>
02 <SECTION> TITLE OF THE INVENTION (DEVICE) </SECTION>
03 <P>
(TAG CODE) (TAG CODE)
(TAG CODE)
DATA COMPRESSING·RECONSTRUCTING METHOD AND APPARATUS AND DOCUMENT MANAGEMENT SYSTEM (TAG CODE)
TAG COMPRESSION
ENCODE CHARACTER TRAIN
OUTPUT
OUTPUT

FIG. 23


CODE STREAM 90
60 TAG INFORMATION SEPARATING UNIT
92 COMPRESSION TAG STORING UNIT
94 TAG INFORMATION RECONSTRUCTING UNIT
62 TAG INFORMATION STORING UNIT
TAG INFORMATION
64
66 CODE TRAIN COMPARING UNIT
65 DICTIONARY STORING UNIT
68 CHARACTER TRAIN REPLACING UNIT
CHARACTER TRAIN STREAM

FIG. 24


CODE STREAM 100
82
CODE SWITCHING UNIT
TAG INFORMATION STREAM
80
CODE STORING UNIT
78
TAG INFORMATION STORING UNIT
98
CODE AMOUNT MEASURING UNIT
16
CHARACTER TRAIN COMPARING UNIT
18
DICTIONARY STORING UNIT
14
22
24
96
TAG DICTIONARY STORING UNIT
97
TAG CHARACTER TRAIN COMPARING UNIT
10
TAG INFORMATION SEPARATING UNIT
12
TAG CODE REPLACING UNIT
CHARACTER TRAIN STREAM 20

FIG. 25


35
<TITLE> SPECIFICATION OF THE INVENTION (DEVICE) </TITLE> <P>
<SECTION> TITLE OF THE INVENTION (DEVICE) </SECTION>
DATA COMPRESSING·RECONSTRUCTING METHOD AND APPARATUS AND DOCUMENT MANAGEMENT SYSTEM <P>
SEPARATE
REPLACE
36
01 <TITLE> SPECIFICATION OF THE INVENTION (DEVICE) </TITLE> <P>
02 <SECTION> TITLE OF THE INVENTION (DEVICE) </SECTION>
03 <P>
38
(TAG CODE) (TAG CODE) (TAG CODE)
DATA COMPRESSING·RECONSTRUCTING METHOD AND APPARATUS AND DOCUMENT MANAGEMENT SYSTEM (TAG CODE)
ENCODE TAG CHARACTER TRAIN
ENCODE CHARACTER TRAIN
OUTPUT
OUTPUT

FIG. 26



FIG. 27



FIG. 28


CODE STREAM 100
TAG INFORMATION SEPARATING UNIT 60
CODE TRAIN COMPARING UNIT 66
DICTIONARY STORING UNIT 65
CHARACTER TRAIN REPLACING UNIT 68
64
CHARACTER TRAIN STREAM
COMPRESSION TAG STORING UNIT 92
TAG CHARACTER TRAIN RECONSTRUCTING UNIT 102
TAG INFORMATION STORING UNIT 62
TAG INFORMATION
TAG RECONSTRUCTION DICTIONARY STORING UNIT 104

PTO/SB/106 (6-96)
Approved for use through 9/30/98. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

Data compressing apparatus, reconstructing apparatus, and its method

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ _月_日に提出され、米国出願番号または特許協定条約国際出願番号を_____とし、
（該当する場合）_____ に訂正されました。

☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第３７編第１条５６項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

PTO/SB/106 (6-95)
Approved for use through 9/30/98. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Japanese Language Declaration
(日本語宣言書)

私は、米国法典第３５編１１９条(a)-(d)項又は３６５条(b)項に基き下記の、米国以外の国の少なくとも一ヵ国を指定している特許協力条約３６５(a)項に基ずく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s) 外国での先行出願 (Number) (番号)	(Country) (国名)	(Day/Month/Year Filed) (出願年月日)	Priority Not Claimed 優先権主張なし
10/272,724	Japan	28/9/98	☐
			☐

私は、第３５編米国法典１１９条(e)項に基いて下記の米国特許出願規定に記載された権利をここに主張いたします。

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.) (出願番号)	(Filing Date) (出願日)	(Application No.) (出願番号)	(Filing Date) (出願日)

私は、下記の米国法典第３５編１２０条に基いて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約３６５条(c)に基ずく権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第３５編１１２条第１項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第３７編１条５６項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of application.

(Application No.) (出願番号)	(Filing Date) (出願日)	(Status: Patented, Pending, Abandoned) (現況：特許許可済、係属中、放棄済)

私は、私自身の知識に基ずいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じるところに基ずく表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第１８編第１００１条に基ずき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに下記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

98-3367

PTO/SB/106 (8-96)
Approved for use through 9/30/98. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration
(日本語宣言書)

委任状： 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。（弁護士、または代理人の氏名及び登録番号を明記のこと）

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith *(list name and registration number)*

James D. Halsey, Jr., 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; John C. Garvey, 28,607; J. Randall Beckers, 30,358; William F. Herbert, 31,024; Richard A. Gollhofer, 31,106; Mark J. Henry, 36,162; Gene M. Garner II, 34,172; Michael D. Stein, 37,240; Paul I. Kravetz, 35,230; Gerald P. Joyce, III, 37,648; Todd E. Marlette, 35,269; Harlan B. Williams, Jr., 34,756; George N. Stevens, 36,938; Michael C. Soldner, 41,455; Norman L. Ourada, 41,235; Kevin R. Spivak, P-43,148; and William M. Schertler, 35,348 (agent)

書類送付先

Send Correspondence to:

STAAS & HALSEY
700 Eleventh Street, N.W.
Suite 500
Washington, D.C. 20001

直接電話連絡先： （名前及び電話番号）

Direct Telephone Calls to: *(name and telephone number)*

STAAS & HALSEY
(202) 434-1500

唯一または第一発明者名		Full name of sole or first inventor: Takashi Morihara
発明者の署名	日付	Inventor's signature: Takashi Morihara Date: 6/7/99
住所		Residence: Kawasaki, Japan
国籍		Citizenship: Japan
私書箱		Post Office Address: c/o FUJITSU LIMITED 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa 211-8588, Japan
第二共同発明者		Full name of second joint inventor, if any: Hironori Yahagi
第二共同発明者	日付	Second inventor's signature: Hironori Yahagi Date: 6/7/99
住所		Residence: Kawasaki, Japan
国籍		Citizenship: Japan
私書箱		Post Office Address: c/o FUJITSU LIMITED 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa 211-8588, Japan

（第三以降の共同発明者についても同様に記載し、署名をすること）

(Supply similar information and signature for third and subsequent joint inventors.)

第三共同発明者		Full name of third joint inventor, if any Noriko Satoh
第三共同発明者	日付	Third inventor's signature Date Satoh Noriko 6/7/99
住　所		Residence Kawasaki, Japan
国　籍		Citizenship Japan
私書箱		Post Office Address c/o FUJITSU LIMITED 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa 211-8588, Japan
第四共同発明者		Full name of fourth joint inventor, if any
第四共同発明者	日付	Fourth inventor's signature Date
住　所		Residence
国　籍		Citizenship
私書箱		Post Office Address

第五共同発明者		Full name of fifth joint inventor, if any
第五共同発明者	日付	Fifth inventor's signature Date
住　所		Residence
国　籍		Citizenship
私書箱		Post Office Address
第六共同発明者		Full name of sixth joint inventor, if any
第六共同発明者	日付	Sixth inventor's signature Date
住　所		Residence
国　籍		Citizenship
私書箱		Post Office Address

（第七以降の共同発明者についても同様に記載し、署名をすること）

(Supply similar information and signature for seventh and subsequent joint inventors.)